

Light efficiency:

41 Lumen/Watt

Light quality:

CRI: 96.5

Color temperature:

3174 K

Output: 2356 lm

Peak: 21953 cd

Power: 57.6 W

PF: 0.98



Tracking number: [n/a](#)

Product name:

ElectraPix Bar 16

Item number:

CRI No Diffusion

Date and time:

8/30/2024 10:05:01 AM

Description:

R @ 155


G @ 36

B @ 30

A @ 255

L @ 255

U @ 0




CIE 1931


x: 0.433

y: 0.416



Spectra




Power




Color details



TM-30: 93.8



CRI: 96.5 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
99.1	96.6	92.8	92.7	98.4	99.1	98.1	95.4	82.8	92.3	86.4	85.3	99.2	94.8	94.5


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
94.5	96.0	94.4	96.7	94.2	92.7	95.6	91.9	95.7	95.7	95.0	89.6	90.9	90.5	92.2	88.3

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
92.2	95.0	95.8	95.1	91.5	90.2	96.6	95.3	92.5	89.2	87.8	90.1	93.2	94.5	93.6

CQS: 92.3



Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3174 K	96.5	82.8	93.8	101.4	92.3	0.433	0.416	0.243	0.350	0.0054

TM-30 details







Rf 93.8

Fidelity index Rf


Rg 101.4

Gamut index Rg

Hue Bin	R _i	Shifts (%)	
		Chroma	Hue
1	95	-2%	-1%
2	96	-1%	-1%
3	94	-1%	0%
4	97	-2%	0%
5	94	-1%	3%
6	93	3%	4%
7	96	2%	0%
8	92	5%	0%
9	96	1%	-1%
10	96	-1%	-1%
11	95	1%	2%
12	90	4%	-4%
13	91	2%	-7%
14	91	3%	-7%
15	92	0%	-4%
16	88	1%	-9%



Beam details



Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
21371lx	5343lx	2375lx	1336lx	855lx	594lx	436lx	334lx	264lx	214lx	177lx	148lx	126lx	109lx	95lx	83lx	74lx	66lx	59lx	53lx
1985.4fcd	496.4fcd	220.6fcd	124.1fcd	79.4fcd	55.2fcd	40.5fcd	31fcd	24.5fcd	19.9fcd	16.4fcd	13.8fcd	11.7fcd	10.1fcd	8.8fcd	7.8fcd	6.9fcd	6.1fcd	5.5fcd	5fcd

Intensities in 0° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
21.4K	20.9K	20.5K	20.0K	19.2K	17.5K	15.9K	14.2K	12.5K	10.9K	9.3K	7.8K	6.3K	4.7K	3.5K	2.9K	2.2K	1.6K	1.0K	0.6K
100%	98%	96%	94%	90%	82%	74%	66%	59%	51%	44%	37%	29%	22%	16%	13%	11%	8%	5%	3%

Intensities in 90° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
21.4K	20.9K	20.5K	20.0K	19.2K	17.5K	15.9K	14.2K	12.5K	10.9K	9.3K	7.8K	6.3K	4.7K	3.5K	2.9K	2.2K	1.6K	1.0K	0.6K
100%	98%	96%	94%	90%	82%	74%	66%	59%	51%	44%	37%	29%	22%	16%	13%	11%	8%	5%	3%

Intensities in 180° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
21.4K	21.8K	21.1K	19.8K	18.6K	17.3K	16.1K	14.4K	12.6K	10.9K	9.1K	7.3K	6.0K	5.0K	4.0K	3.0K	1.9K	1.4K	1.2K	0.9K
100%	102%	99%	93%	87%	81%	75%	68%	59%	51%	42%	34%	28%	23%	19%	14%	9%	7%	5%	4%

Intensities in 270° c-plane


0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
21.4K	21.8K	21.1K	19.8K	18.6K	17.3K	16.1K	14.4K	12.6K	10.9K	9.1K	7.3K	6.0K	5.0K	4.0K	3.0K	1.9K	1.4K	1.2K	0.9K
100%	102%	99%	93%	87%	81%	75%	68%	59%	51%	42%	34%	28%	23%	19%	14%	9%	7%	5%	4%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
17.9°	31.8°	39.5°	99.9%	99.2%


Flicker

Flicker curve (complete sampled flicker signal)

Flicker frame (frame of one flicker period)



Flicker FFT (frequency scope of flicker curve)



Flicker results:

Flicker frequency:		1176.47 Hz	
Flicker index:	0.15	JA8/10 40Hz	0.77 %
Flicker percentage:	65.1 %	JA8/10 90Hz	1.73 %
SVM: (Visual flicker)	0.49	JA8/10 200Hz	3.78 %
PstLM	0.05	JA8/10 400Hz	7.37 %
Mp	0.14	JA8/10 1000Hz	18.89 %

Flicker conditions:

Sample rate:	20000 samples/second
--------------	----------------------