



Light efficiency:


18 Lumen/Watt

Light quality:

CRI: 0.0

Color temperature:

0 K



Product name:

7PZ IP

Test:


Zoom Out Full On

Date:


4/21/2017

Output: 2266 lm Power consumption: 124 W Peak: 10927 cd


Spectral distribution




Color coordinates



Zoom color point




CRI R values



Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color divition from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
0 K	0.0	0.0	0.0	0.0	0.0	0.229	0.209	0.181	0.248	n/a

## Beam details



## Beam angles

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%
25.2°	41.9°	54°

## Beam intensities

Peak intensity	Int. ratio in 120° cone	Int. ratio in 90° cone
10927 cd	1.0%	1.0%

## Power

Power	Power factor	Power frequency
124 W	0.97	59.9 Hz

Nominal voltage	Voltage	Current
230 V	116 V	1.10 A

## Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
10909lx	2727lx	1212lx	682lx	436lx	303lx	223lx	170lx	135lx	109lx	90lx	76lx	65lx	56lx	48lx	43lx	38lx	34lx	30lx	27lx
1013.5fcd	253.4fcd	112.6fcd	63.3fcd	40.5fcd	28.2fcd	20.7fcd	15.8fcd	12.5fcd	10.1fcd	8.4fcd	7fcd	6fcd	5.2fcd	4.5fcd	4fcd	3.5fcd	3.1fcd	2.8fcd	2.5fcd